
## KM-757 / 757BL Series

High Speed, 2-Needles, Needle Feed, Lock Stitch Sewing Machine with Automatic Thread Trimmer



### **Specification**

Model	KM-757-7S	KM-757BL-7S								
Application	Medium Materials and Heavy Materials									
Max. Sewing Speed	3,000spm									
Max. Stitch Length	5mm	7mm								
Needle Bar Stroke	33.4mm									
Thread Take-up Stroke	57.2mm	62.1mm								
Height of Presser Foot	Hand : 7mm / Knee : 15mm									
Foot(Automatic)	15mm(Optional Among Trimming Types)									
Hook	Horizon Standard Hook	Horizon Double - Capacity Rotary Hook								
Needle	DP×5 #14(#11~#22)	DP×5 #22(#11~#22)								
Trimming Device	Trimming (7S) : Servo Motor									
Motor	Non - Trimming(No Mark) : Clutch Motor									

### **Option Gauge**

\* In case of using over 1-1/2"(38.1mm) guage parts, it is required to make special matching on the arm bed.

Spec.	1/16″	3/32″	1/8″	5/32″	3/16″	1/4″	5/16″	3/8″	7/16″	1/2″	5/8″	3/4″	7/8″	1″	1-1/4″	1-3/8″	1-1/2″	2″	2-1/16″
Model	1.6mm	2.4mm	3.2mm	4mm	4.8mm	6.4mm	7.9mm	9.5mm	11mm	12.7mm	15.9mm	19mm	22.2mm	25.4mm	31.8mm	34.9mm	38mm	50.8mm	52.4mm
KM-757	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	*	*
KM-757-7S/7N	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	*	
KM-757BL	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
KM-757BL-7S/7N	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		

### Application

A needle feed sewing machine that is completely free from unevenness in material feed and material puckering, suitable to fancy stitching for jeans, vinyl or leather, etc. \* Specifications and appearance are subject to change for the improvement of products without prior notice.

### OVERSEAS MARKETING DIVISION

#178-212, GAJWA-DONG, SEO-GU, INCHEON, KOREA TEL: 82-32-580-5741~60 FAX: 82-32-584-3025~6

#### **OVERSEAS NETWORK**

SUNSTAR U.S.A INC TEL: 1-305-591-9596 FAX: 1-305-591-0661 | SUNSTAR DO BRASIL LTDA | TEL: 55-11-3362-3434 FAX: 55-11-3362-3444 SUNSTAR MACHINERY EUROPE GMBH TEL: 43-2236-660-229 FAX: 43-2236-660-2293 | SUNSTAR MACHINERY (SINGAPORE)PTE LTD. | TEL: 65-6227-7545 FAX: 65-6227-7905 | SUNSTAR JAKARTA BRANCH OFFICE | TEL: 62-21-4586-5839 EAX: 62-21-4586-5840

SunStar CO., LTD.

| SUNSTAR DHAKA BRANCH OFFICE | TEL: 88-02-881-9153 FAX: 88-02-883-5707 | SUNSTAR CHITTAGONG BRANCH OFFICE | TEL & EAX: 88-031-255-2497 SUNSTAR BANGALORE BRANCH OFFICE TEL: 91-080-2653-0365/2653-0366 FAX: 91-080-2653-0367 | SUNSTAR DELHI BRANCH OFFICE | TEL: 91-11-4057-4207/4208/4209 FAX: 91-11-4057-4235 | SUNSTAR HOCHIMINH BRANCH OFFICE | TEL: 84-8-3592-3703 FAX: 84-8-3592-3704 SUNSTAR HANOI BRANCH OFFICE TEL · 84-4-3783-1446 EAX· 84-4-3783-1447

### **OVERSEAS NETWORK**

| SUNSTAR MACHINERY(SHANGHAI) CO., LTD. | TEL: 86-21-6957-6308~6312 FAX: 86-21-6957-6093 I SUNSTAR MACHINERY(SHANGHAI) CO., LTD. MARKETING DIVISION TEL: 86-21-6353-2233 FAX: 86-21-6353-8640 | SUNSTAR QINGDAO BRANCH OFFICE | TEL: 86-532-6691-1236 FAX: 86-532-6691-2262 | SUNSTAR NANJING BRANCH OFFICE | TEL: 86-25-8459-4758 FAX: 86-25-8459-4408 | SUNSTAR HANGZHOU BRANCH OFFICE | TEL: 86-571-8577-9479 FAX: 86-571-8577-9478 SUNSTAR JINAN BRANCH OFFICE TEL: 86-531-8592-8258 EAX: 86-531-8592-8358

SUNSTAR DONGGUAN BRANCH OFFICE TEL: 86-769-2234-4043 FAX: 86-769-2234-4042 SUNSTAR FUJIAN BRANCH OFFICE TEL: 86-595-8859-8871 EAX: 86-595-8859-8872 | SUNSTAR ANHUI BRANCH OFFICE | TEL & FAX: 86-551-424-8000 | SUNSTAR WUHAN BRANCH OFFICE | TEL: 86-27-8375-3080 FAX: 86-27-8375-0371

WEB - SITE	
http://sunstar.co.kr	
E - MAIL	
marketingðsunstar og kr	





# **KM-757/757BL Series**

High Speed, 2-Needles, Needle Feed, Lock Stitch Sewing Machine with Automatic Thread Trimmer




## **KM-757/757BL Series**

### High Speed, 2-Needles, Needle Feed, Lock Stitch Sewing Machine with Automatic Thread Trimmer

### New, Twin Needle Sewing Machine Series Developed Through The Advanced Technology of SunStar!

A new, higher level of advanced mechatronics has been ideally achieved by the grafting of the newly developed, automatic thread trimming FORTUNA III AC SERVO MOTOR, equipped with the most up-to-date function, to our new twin-needle sewing machine ; varied functions created for operational convenience. This new product will contribute greatly to upgrading variable of sewing pattern quality and to increased productivity.



### >> Solenoid-based thread release structure

The length of the remaining upper thread after trimming can be freely adjusted by controlling the control box volume (KM–757(BL)–7S(N)).



### >> Large hook installation

Owing to the fitting of a large hook, double quantity of lower threads can be secured promoting work efficiency (BL type) compared to normal hook.

### >> Built-in synchronizer

Synchronizer installed in pulley is more simple and adjusted easily, (KM-757(BL)-7S)

### >> Convenient bobbin <u>thread check system</u>

Thread remaining in the bobbin can be verifed easily through inspection windows installed on the left and right sides of each board.

### > Thread trimming Mes structured for high reliability and wide operating periphery

- Because the Mes is structured to offer a long-life. Plane surface action capable of perfectly cutting thin or thick thread, no Mes re-adjustment is required at all when stitch lengths are changed.
- The wide operating periphery of the thread trimming Mes makes for easy assembly and disassembly. (KM-757(BL)-7S(N))

### >> Separated adjustment of left and right thread tension

The thread adjusting device is able to control the tension of left and right upper threads separately. In any condition, clean and high-quality sewing is guaranteed.